### 800X2400mm 1200X2400mm



## **COLLECTION 2020**

# Fab Slab



Fab Slab is a flourishing centre for Italian design and slabs. Fab Slab is a new conglomerate that offers a rich array of products and services in terms of design and manufacturing of slabs. Fab Slab represents unperalleled technical, artistic and organizational standards that distinguish it from its peers.

Fab Slab is the essence of years of rigorous research. In it's core efforts, Fab Slab epitomizes the urge to establish new standards and norms in the industry. Over decades of experience has gone into the making of this ambitious venture that us set to revolutionize art and craft of manufacturing slabs. Based on ground-breaking research, Fab Slab has conceptualized it's ravishing designs and world-class manufacturing process.






## WHAT IS Fab Slab?

STRENGTH PLUS VERY LARGE SIZES AND HIGH THICKNESS.

An innovative and Italian quality porcelain slabs, ideal for kitchen countertops, bathroom countertops, furniture, flooring and wall applications. The perfect combination of quality and wide collections of texture surface like marble, stone, wood, metal & concrete.





Specific answers to any need. **5 sizes, 4 thickness op⊠ons** 

## APPLICATION





.



FITTED KITCHEN AND BATHROOM FURNITURE HOTELS

ň Iľ

SPA AND WELLNESS

CENTRES

RETAIL MALLS





OFFICES



MUSEUMS



VENTILATED CURTAIN WALLS







## NEW PRODUCTION TECHNOLOGIES BRING UP THE CHALLANGE OF CREATING MATERIALS CAPABLE OF SHAPING THE SPACE TECHNICALLY AND ESTHETICLY IN AN EFFICIENT WAY.

Fab Slab, a brand born to provide advanced solutions to architecture and interior design. Materials that offer unlimited versatility in all fields of construction, furniture, design, etc.

## **FEATURES**



## POSSIBILITIES



**APUANE STATUARIO** 







#### **BLUE PEARL**

\_\_\_\_






#### **CRYSTAL ONYX**



—

#### **ESSEL BROWN**



THICKNESS

15MM, 18 MM

SIZE

—

800X2400MM 1200X2400MM

FINISH

\_

GLOSSY

EFFECT

**GLASS WHITE** 



THICKNESS

15MM, 18 MM

SIZE

-

800X2400MM 1200X2400MM

FINISH

\_

GLOSSY

EFFECT

**IMPERIAL WHITE** 


#### **GOLDEN PORTORO**











THICKNESS

15MM, 18 MM

SIZE

—

800X2400MM 1200X2400MM

FINISH

\_

GLOSSY

EFFECT

#### MARBLE VOLAKAS






#### LABRADOR BLACK











THICKNESS

15MM, 18 MM

SIZE

—

800X2400MM 1200X2400MM

FINISH

\_


GLOSSY

EFFECT

#### STATUARIO LUCIDATO

**STATUARIO PEARL** 









THICKNESS -15MM, 18 MM

SIZE

\_

\_

800X2400MM 1200X2400MM

FINISH

GLOSSY

EFFECT



#### TERAZZO BROWN SALT N PPEPPER



THICKNESS

15MM, 18 MM

SIZE

800X2400MM 1200X2400MM

FINISH

\_

GLOSSY

EFFECT

TERAZZO GREY SALT N PEPPER





TERAZZO IVORY SALT N PEPPER

THICKNESS

15MM, 18 MM

SIZE

800X2400MM 1200X2400MM

FINISH

\_

GLOSSY

EFFECT

#### TERAZZO VERDE SALT N PEPPER









THICKNESS

15MM, 18 MM

SIZE

800X2400MM 1200X2400MM FINISH — GLOSSY EFFECT — MARBLE


## TECHNICAL SPECIFICATION


| CHARACTERISTICS               | STANDARD AS PER<br>ISO-13006/En14411 GROUP | VALUES        | TEST METHOD    |
|-------------------------------|--|---------------|----------------|
|                               | REGULATORY PR                              | OPERTIES      | 1              |
| Deviation in Lenth & Width    | 0.50%                                      | 0.20%         | ISO - 10545-2  |
| Deviation in Thickness        | 0.50%                                      | 0.50%         | ISO - 10545-2  |
| Straightness of Sides         | 0.50%                                      | 0.20%         | ISO - 10545-2  |
| Rectangularity                | 0.50%                                      | 0.20%         | ISO - 10545-2  |
| Surface Flatness              | 0.50%                                      | 0.20%         | ISO - 10545-2  |
| Color Difference              | Unaltered                                  | No Change     | ISO - 10545-16 |
| Glossiness                    | As per Mfg.                                | >90%          | Glossmeter     |
|                               | STRUCTURAL PR                              | OPERTIES      |                |
| Water Absorption              | <0.05%                                     | <0.05%        | ISO - 10545-3  |
| Apparent Density              | >2.00 g/cc                                 | >2.10 g/cc    | DIN 51082      |
|                               | MASSIVE MECHANICA                          | AL PROPERTIES |                |
| Modulus of Repture            | Min 35N/MM2                                | Min 40N/MM2   | ISO - 10545-4  |
| Breaking Strength             | Min. 1300 N                                | Min. 2000 N   | ISO - 10545-4  |
| Impact Resistance As per Mfg. |  | Min. 0.55     | ISO - 10545-5  |
|                               | SURFACE MECHANICA                          | AL PROPERTIES |                |
| Surface Abrasion Resistance   | As per Mfg.                                | Min. class 3  | ISO - 10545-7  |
| Moh's Hardness                | As per Mfg.                                | Min. class 4  | EN 101         |
|                               | THERMO HYGROMETR                           |               |                |
| Frost Resistance              | No Damage                                  | No Damage     | ISO - 10545-12 |
| Thermal Shock Resistance      | No Damage                                  | No Damage     | ISO - 10545-09 |
| Moisture Expansion            | Nil  | Nil           | ISO - 10545-10 |
| Thermal Expansion             | Max 9.0x10 -6                              | Max 6.5x10 -6 | ISO - 10545-08 |
| Crazing Resistance            | As per Mfg.                                | Min 10 Cycle  | ISO - 10545-11 |
|                               | CHEMICAL PRO                               | PERTIES       |                |
| Chemical Resistance           | No Damage                                  | No Damage     | ISO - 10545-13 |
|                               |  |               |                |


## SAFETY PROPERTIES Slip Resistance As per Mfg. >0.40 ISO - 10545-17 Fire Resistance As per Mfg. Fire Proof N.A.

## PACKING DETAIL

| SIZE (in mm) | THICKNESS APPROX | PIECES / PER BOX | COVERAGE AREA IN SQ. FT | BOX WEIGHT ( APPROX. ) |
|--------------|------------------|------------------|-------------------------|------------------------|
| 800x2400 MM  | 15 MM            | 1                | 20.67                   | 68 kgs                 |
| 800x2400 MM  | 18 MM            | 1                | 20.67                   | 81 kgs                 |












RIGHT



#### STORAGE

We should use a forklift truck, at least 2,5 mts. long, with the forks positioned in the largest width position, in order to handle the pallet on a proper way. Under normal conditions, the forks are positioned in the mid dle of the long side of the pallet, as they must hold the whole depth of the pallet. To allow the extraction of the slabs in a safe and easy way, it is recommended to position the pallets in a suitable area where the lift truck can be moved around all sides of the pallet.





#### HANDLING SLAB

Fab Slab's extra-large format slabs arrived in oversized crates, which require specific handling equipment. To prevent damage from occurring during forklift operation, specific fork sizes must be used. For example, to handle a create of 135cm x 305cm tiles from the side, 112cm/44" long forks are recommended.

To handle the same create from the narrow end requires forks that are at least 213cm/84" long. Lifting multiple crates with longer forks may require forklifts with a greater lift capacity.

Specialized tools and equipment are currently available for the handling and installation of large porcelain surfaces. Innovative trowels with unique notch configurations can help increase the consistency of the mortar coverage on the back of the tile.

**LEVELLING EQUIPMENT** 

RLS Clips for Tiles 10-12 MM thick (½" - ¾")


Wedges in 1000 pcs / carton

Adjustable pliers for wall

and floor covering


- 400 pcs bag


#### HANDLING EQUIPMENT



Double Suction Cup 115 MM 📜







Free cut guide with complete outfit Max. cut of length-156 CM

Free cut extension length - 170 CM

Cutting of pillars for tiles/slabs

#### **MECHANICAL FIXING EQUIPMENT**

Fix Stainless Steel Hook for 8 MM thickness tiles - 500 pcs



Cut Grooving Machine 850w-230v 50/60hz



Thickness 6-12 MM

**CUTTING EQUIPMENT**